

DC power supply linear regulated for 115 / 230VAC input voltage type PSLC1



CE - konform

Technical data

Input data		
Input voltage AC	115Volt / 230Volt	45 - 66 Hz
Inputvoltage tolerance	-15% to +15%	
Input current at nominal load	at 115VAC max. 330mA / at 230VAC max. 165mA	
Input current peak	-	
Protective circuit	-	
Hold-up time	20 mSek. typ.	
Output data		
Output voltage $U_{Nominal}$	see table below	
Output current $I_{Nominal}$	see table below	
Current limiting	1,1 x I_N	
Residual ripple (100Hz)	< 10mV	
Control data		
Control deviation load	< 200mV with load variation 10...90%	
Control deviation supply	< 10mV with supply variation \pm 10%	
Control time	< 50 μ Sek. with load variation 10...90%	
Operating data		
Duty circle	100%	
Operating temperature range	-30°C to +80°C	
Derating	from 40°C	
Storage temperature range	-30°C...+105°C	
Cooling	selfcooling	
	recommended respective distance 15mm each	
Safety devices		
Fuse for input	at 115VAC 0,5A delayed / at 230VAC 0,25A delayed	
Fuse for output	not necessary - cont. short-circuit proof	
Overload protection	integrated into device	
MTBF	>380.000 h	
Safety data		
Test voltage transformer	5 kVac in accordance to VDE 0551	
High voltage resistance	Primary circuit - secondary circuit 3,75 kVac acc. to VDE 0806 / IEC 380	
Degree of EMI suppresion	in acc. to VDE 0871 B, EN 55022/B	
Protection class	Class 2 (EN 60950)	
Extra low safety potential	PELV (EN60204), SELV (EN 60950)	
Ambient humidity	95% relative humidity, yearly average dewing allowed for use in tropical ambient	
Protective class enclosure	IP 65	
Protective class terminals	IP 20 (VGB4)	
Vibration proof	>30g at 33Hz in X,Y and Z, acc. to IEC 60068-2-27	
Applied construction regulations		
according to VDE	VDE 0100, 0110, 0113, 0551, 0160/W2, 0806	
IEC	IEC 60950, IEC61000-6-1-2-3-4, IEC60068-2-3	
	IEC 60068-2-11-52, IEC 60529, IEC 380	
EN	EN60950, EN50081-1, EN50081-2, EN50082-1	
	EN61000-6-1-2-3-4, EN50178, EN55022	
	EN55011, EN61000-3-3, EN50204, EN61558-2-17	
	EN60204, EN60529, EN61000-4-2-3-4-5-6-8-11	
	EN60068-1, EN60068-2-1-2-3-6-27-30	
	EN45501, EN50021	
CSA / UL	CSA-C 22.2 / UL60950, UL508, UL1950	
Mechanics		
Mounting	On rails acc. to DIN46277 or wall mounting with screws	

- Output separated according to VDE 0551
- Extra low safety potential PELV (EN 60204), SELV (EN 60950)
- Overload- and open circuit protected short circuit proof
- Parallel connection possible Protected against pol-permutation at the output
- Suitable for the tropics - Epoxy resin casted
- Operating status shown by LED
- Safety acc. to VDE, EN, UL, CSA

Nominal output voltage	5,0Vdc	12,0Vdc	15,0Vdc	24,0Vdc
Range of adjustment output voltage	-	-	-	-
Type	PSLC051	PSLC121	PSLC151	PSLC241
Nominal output current	1,0Amp.	1,0Amp.	1,0Amp.	1,0Amp.
Power	5Watt	12Watt	15Watt	24Watt
Efficiency	29%	42%	48%	58%
Dimensions (W x H x D)	55x75x110	55x75x110	55x75x110	55x75x110
Weight	approx. 0,84kg	approx. 0,84kg	approx. 0,84kg	approx. 0,84kg
Order-No.	58006	58026	58016	58025

